

# Residential Power Optimiser

## For Australia

S440 / S500 / S500B / S650B



POWER OPTIMISER

### PV power optimisation at the module level

- Specifically designed to work with SolarEdge inverters
- Flexible system design and compatible with bifacial PV modules for maximum space utilisation
- Detects abnormal PV connector behaviour, preventing potential safety issues\*
- Faster installations with simplified cable management and easy assembly using a single bolt
- Module-level voltage shutdown for installer and firefighter safety
- Next generation maintenance with module safety
- Superior efficiency (99.5%)
- Mitigates all types of module mismatch-loss, from manufacturing tolerance to partial shading

\* Functionality subject to inverter model and firmware version

# / Residential Power Optimiser

## For Australia

S440 / S500 / S500B / S650B

	S440	S500	S500B	S650B	Units
<b>INPUT</b>					
Rated Input DC Power <sup>(1)</sup>	440 <sup>(2)</sup>	500		650	W
Absolute Maximum Input Voltage (Voc)	60		125	85	Vdc
MPPT Operating Range	8 – 60		12.5 – 105	12.5 – 85	Vdc
Maximum Short Circuit Current (Isc) of Connected PV Panel	14.5	15			Adc
Maximum Efficiency			99.5		%
Weighted Efficiency			98.8		%
Overvoltage Category			II		
Input Overcurrent Protection			15		Adc
<b>OUTPUT DURING OPERATION</b>					
Maximum Output Current			15		Adc
Maximum Output Voltage	60		80		Vdc
<b>OUTPUT DURING STANDBY (POWER OPTIMISER DISCONNECTED FROM INVERTER OR INVERTER OFF)</b>					
Safety Output Voltage per Power Optimiser			1 ± 0.1		Vdc
<b>STANDARD COMPLIANCE</b>					
EMC			FCC Part 15 Class B; IEC 61000-6-2; IEC 61000-6-3		
Safety			IEC 62109-1 (class II safety); UL 1741		
Material			UL 94 V-0, UV Resistant		
RoHS			Yes		
Fire Safety			VDE-AR-E 2100-712:2018-12		
<b>INSTALLATION SPECIFICATIONS</b>					
Maximum Allowed System Voltage			1000		Vdc
Dimensions (W x L x H)			129 x 155 x 30	129 x 165 x 45	mm
Weight			720	790	gr
Input Connector			MC4 <sup>(3)</sup>		
Input Wire Length			0.1		m
Output Connector			MC4		
Output Wire Length			(+ ) 2.3, (- ) 0.10		m
Operating Temperature Range <sup>(4)</sup>			-40 to +85		°C
Protection Rating			IP68 / NEMA6P		
Relative Humidity			0 – 100		%

(1) Rated power of the module at STC will not exceed the Power Optimiser Rated Input DC Power. Modules with up to +5% power tolerance are allowed.

(2) For installations after April 1st, 2024, the Rated Input DC Power for S440 is 480W.

(3) For other connector types please contact SolarEdge. Please note that with other connector types, the wire length will be 0.16m. The Sense Connect feature will not detect thermal events on these connectors.

(4) Power derating is applied for ambient temperatures above +85°C for S440 and S500, and for ambient temperatures above +75°C for S500B and S650B. For details, refer to the [Power Optimisers Temperature Derating](#) technical note.

PV System Design Using a SolarEdge Inverter <sup>(5)</sup>	SolarEdge Home Genesis / SolarEdge Home Hub	Three Phase Residential	Three Phase Commercial	Units
Minimum String Length (Power Optimisers)	S440, S500 S500B, S650B	8 6	9 8	16 14
Maximum String Length		25	25	50
Maximum Nominal Power per String		5700	5625	11,250
Maximum Allowed Connected Power per String <sup>(6)</sup> (In multiple string designs, the maximum is permitted only when the difference in connected power between strings is 2,000W or less)		6800 <sup>(7)</sup>	6800 <sup>(7)</sup>	13,500 <sup>(8)</sup>
Parallel Strings of Different Lengths or Orientations		Yes		

(5) It is not allowed to mix S-series and P-series Power Optimisers in new installations in the same string.

(6) If the inverter's rated AC power ≤ maximum nominal power per string, then the maximum connected power per string will be able to reach up to the inverter's maximum input DC power. For details, refer to the [Single String Design Guidelines](#) application note.

(7) For inverters with a rated AC power ≥ 7000W that are connected to at least two strings.

(8) In multiple string designs, it is allowed to install up to 13,500W per string when the difference in the connected power between strings is 2000W or less.

