

---

# Backup Interface

## for Australia

# HOME BACKUP



## Backup Interface for Flexible Backup

- Automatically provides backup power to home loads in the event of grid interruption
- Full flexibility in which loads to back up – the entire home or selected loads
- Scalable solution to support higher power & higher capacity<sup>(\*)</sup>
- Seamless integration with the Energy Hub Inverter with Prism Technology to manage and monitor both PV generation and energy storage
- Generator connection support

\* Requires supporting inverter firmware

# / Backup Interface For Australia

Part Number	BI-NAUGN-01	Units
Model Number	BI-AU1P	
<b>INPUT FROM GRID</b>		
AC Current Input	100	A
AC Output Voltage (Nominal)	230	Vac
AC Output Voltage Range	160 - 264	Vac
AC Frequency (Nominal)	50	Hz
AC Frequency Range	45 - 55	Hz
Microgrid Interconnection Device Rated Current	100	A
Grid Disconnection Switchover Time	<3	sec
<b>OUTPUT TO MAIN DISTRIBUTION PANEL</b>		
Maximum AC Current Output	100	A
AC Frequency (Nominal)	50	Hz
AC Frequency Range	45 - 55	Hz
Maximum Inverters AC Current Output in Backup Operation	100	A
AC L-N Output Voltage in Backup (Nominal)	230	V
AC L-N Output Voltage Range in Backup	160 - 264	V
AC Frequency Range in Backup	45 - 55	Hz
Overvoltage Category	III	
<b>GENERATOR<sup>(1)</sup></b>		
Maximum Rated AC Power	17250	W
Maximum Continuous Input Current	75	Aac
Dry Contact Switch Voltage Rating	250/30	Vac/Vdc
Dry Contact Switch Current Rating	5	A
2-wire Start Switch	Yes	
<b>ADDITIONAL FEATURES</b>		
Installation Type	Suitable for use as service equipment	
Number of Communication Inputs	1	
Communication	RS485	
Energy Meter (for Import/Export)	1.25% accuracy	
Manual Control Over Microgrid Interconnection Device	Yes	
<b>STANDARD COMPLIANCE</b>		
Safety	IEC/EN 62109-1	
Emissions	AS/NZS CISPR 32	
<b>STANDARD COMPLIANCE</b>		
Supported Inverters	StorEdge single phase inverter, Single phase Energy Hub inverter with Prism technology	
AC From Grid Conductor Cable Area	6 - 16	mm <sup>2</sup>
Grid / Loads Conduit Size	25 - 32	mm
AC Conductor Cable Area	4 - 10	mm <sup>2</sup>
Generator Conductor Cable Area Range	4 - 16	mm <sup>2</sup>
Generator Conduit Size	25-32	mm
Communication Cable Conductor Area	0.02 - 1.5	mm <sup>2</sup>
Communication Gland Size	5-15	mm
Weight	<4	kg
Noise	< 50	dBA
Operating Temperature Range	-40 to +50	°C
Relative Humidity Range	0-100	%
Protection Rating	IP65	
Dimensions (H x W x D)	390 x 238 x 147	mm
Environmental Category	Outdoor	
Pollution degree	3	
Maximum Altitude Rating	2000	

(1) Requires supporting inverter firmware